

INSTITUTIONAL RUBBER WHEELS

Richmond's Institutional Rubber Wheels are attractive grey wheels with non-marking rubber tyres.

Features include sealed bearing and matching grey nylon threadguards for added protection. Models marked with * come with chrome threadguards which are ideal for use in hospitals, schools, home use & light industrial applications.



IR4007



SPECIFICATIONS

						
Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Load Capacity	Wheel Code
75	30	41	5/16" or 3/8"	Ball	80/45	IR3008
75	25	25	1/4"	Ball	100/80	IR3301
100	32	41	5/16" or 3/8"	Ball	100/80	IR4007
100	27	27	5/16" or 8mm	Ball	100/80	IR4401*
125	32	41	5/16"	Ball	100/80	IR5004*
125	32	41	5/16" or 3/8"	Ball	100/80	IR5007
150	32	39.6	5/16"	Ball	100/80	IR6009

ANTI-STATIC (CONDUCTIVE) RUBBER WHEELS

Anti-Static Rubber Wheels provide a surface resistivity of less than 10,000 Ω (OHM). The resistance can increase as a result of mechanical influence. The wheels conform to AS 2050 1978.

We also produce a large range of anti-static (conductive) polyurethane wheels.



AS5005



SPECIFICATIONS

						
Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Load Capacity	Wheel Code
100	32	41	5/16"	Ball	100/80	AS4005
125	32	41	5/16"	Ball	100/80	AS5005