

# STAINLESS STEEL EXCEL BOLT HOLE SERIES

UP TO 300KG / CASTOR

Heavy duty pressed stainless steel frame combined with full stainless componentry make the Excel Series the ideal choice for use in wet areas, frequent wash down applications and food and health industries.

When hygiene is of the utmost importance, the castor has the ability to be fitted to an array of equipment and trolleys with various fittings including; pre fitted threaded inserts, solid drilled metal pintles, expanding pintles or a single bolt or plate style.



S4146B

SUITABLE FOR WET ENVIRONMENTS  
FULL STAINLESS CONSTRUCTION

## SPECIFICATIONS & FITTINGS

 Diameter (mm)	 Width (mm)	 Wheel Type	 Wheel Code	 Bearing Type	 Load Capacity	 Height (mm)	 Swivel Radius	 With Brake	 Bolt Size (mm)	 Swivel Code
100	35	Reb Poly	RP4072	SS Roller	150/110	130	90	125	12	S4148
100	35	GF Nylon	GF412	Plain	200/150	130	90	125	12	S4136
100	35	Nylon	NY401	Plain	200/110	130	90	125	12	S4146
125	35	Reb Poly	RP5072	SS Roller	200/150	157	112	125	12	S5148
125	35	Nylon	NY501	Plain	200/150	157	112	125	12	S5146
150	40	Reb Poly	RP6072	SS Roller	300/225	183	127	127	12	S6148
150	50	Nylon	NY652	Plain	300/225	183	127	127	12	S6146
150	50	Nylon	NY655	SS Roller	300/225	183	127	150	12	S6150

To order castor with Swivel Lock & Brake, add B to the end of the Swivel Code, eg S4146B indicates a brake castor.  
 Indicates castor suitable for high/low temperature applications.

## NYLON EXPANDING PINTLES

Pintle	Pintle Code	Pintle Type
	IPN12-P1	For 19mm ID Round Tube
	IPN12-P2	For 22mm ID Round Tube
	IPN12-P3	For 28.5mm ID Round Tube
	INP12-P4	For 19mm ID Square Tube
	IPN12-P5	For 22mm ID Square Tube
	IPN12-P6	For 28.5mm ID Square Tube
	Single Bolt Fitting Various bolt lengths available	

\*Also see page 92 for Solid and Threaded pintle options



S4148B

S6146

## CASTOR FITTING REQUIREMENTS

To fit to 20mm thick base requires a 50mm x 12mm stainless steel set screw.